



**Test Report**

No.: SHHG1105013179IP

Date: JUL.01,2011

Page: 1 of 6

SJC BRANDS PTY LTD  
9 LINCOLN STREET MINTO. NSW AUSTRALIA 2566

The following sample(s) was/were submitted and identified by the client as:

Sample Description : SLIDE PINE BABY COT FOR HOUSEHOLD USE  
 Style/ Item No. : TUSCANY COT  
 Buyer : SJC BRANDS PTY LTD  
 Manufacturer : DALIAN GUANGMING FURNITURE CO., LTD  
 Country of Origin : CHINA  
 Country of Destination : AUSTRALIA  
 Sample Receiving Date : MAY.31,2011  
 1<sup>st</sup> Resubmitted Sample Date: : JUN.27,2011  
 Further information : JUN.27,2011  
 Testing Period : MAY.31,2011 TO JUN.30,2011  
 Test Performed : SELECTED TEST(S) AS REQUESTED BY APPLICANT  
 Test Requested : AS/NZS 2172:2010 COTS FOR HOUSEHOLD USE --  
 SAFETY REQUIREMENTS-EXCLUDING CLAUSES 4.3  
 Test Result(s) : FOR FURTHER DETAILS, PLEASE REFER TO THE  
 FOLLOWING PAGE(S)  
 Conclusion : THE SUBMITTED SAMPLE MET THE TEST  
 REQUIREMENT OF REQUESTED TEST ITEMS.

\*\*\*\*\*

Signed for and on behalf of  
SGS-CSTC Ltd.

Roy Chen  
Section Manager

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [http://www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its inspection only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755)83071443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.  
Testing Center

3<sup>rd</sup> Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233  
中国·上海·徐汇区宜山路889号3号楼 邮编:200233

t (86-21)61402666\*2013 f (86-21)54500353  
t (86-21)61402666\*2013 f (86-21)54500353

**SHHG 810609**

[www.cn.sgs.com](http://www.cn.sgs.com)  
[sgs.china@sgs.com](mailto:sgs.china@sgs.com)

**Test Conducted:**

**AS/NZS 2172:2010 Cots for Household Use --Safety Requirements -Excluding Clauses 4.3**

1. Scope:

This Standard specifies safety requirements for cots. These include material, design, construction, performance, labelling and marking requirements, all of which are important for the well-being of children who use cots. The Standard is applicable to cots for use in household situations. It is not applicable to most types of folding cots. Folding cots are covered in AS/NZS 2195, however, timber folding cots or cots made with rigid materials are required in AS/NZS 2195 to comply with all applicable requirements of this Standard. Requirements for cots in day nurseries, hospitals and institutions are given in AS/NZS 2130.

2. Number of test sample: 1 Piece of sample packaged

3. Number of Resubmitted sample : Dropside component

4. Mattress size recommended by manufacturer:750mm×1310mm×120mm

5. Internal size of the cot: 775mm×1320mm

6. Test Result: Details Shown As Following Table:

Clause	Test Method/ Requirement	Rating
4	Materials	
4.1	Timber a) Not contain splinters, loose knots, compression failures, pith or reaction wood as defined in AS/NZS 4491. b) Be free from decay and insect attack; and c) Be free from the intentional addition of hazard chemicals such as copper chrome arsenate.	Pass
4.2	Metals All the metal parts shall be either made of corrosion-resistant material or be protected form corrosion.	Pass
4.3	Toxicological requirement All exposed surface of the cot shall comply with the toxicological requirement specified in AS/NZS 8124.3	N/C
5	Construction	
5.1	General	
5.2	Small parts Removable components and components that detach during testing in accordance with Appendices B to F, H and I shall not fit entirely into the small parts cylinder when tested in accordance with Appendix J.	Pass
5.3	Open-ended tubes There shall be no open-ended tubes.	Pass
6	Design	

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755)83071443, or email: CN.Doccheck@sgs.com

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [http://www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions of Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and, within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Clause	Test Method/ Requirement	Rating
6.1	<b>Dimensions</b> <b>a</b> Fix base cots: The vertical distance between the top of the mattress base and top edge of the lowest cot side or end when: 1) The access is closed shall not be less than 600 mm. 2) The access is open shall not be less than 250 mm.	N/A
	<b>b</b> Adjustable base cot: The vertical distance between the top of the mattress base and top edge of the lowest cot side or end when: 1 lower position: 1) the access is closed shall not be less than 600 mm. 2) the access is open shall not be less than 250 mm. 2 upper position 1) the access is closed shall not be less than 400 mm. 2) the access is open shall not be less than 250 mm.	Pass
	<b>c</b> The distance between adjacent filler bars or filler bars and filler panel shall be not less than 50 mm.	Pass
	<b>d</b> Distance between mattress and any part of the cot sides or ends at its centred measured horizontal shall be not more than 20mm.	Pass
	<b>e</b> Distance between the bottom rail of the dropside and the mattress base measured horizontal with the mattress base in the lower position and the dropsied in the closed position shall be not less than 12 mm and not more than 30 mm.	Pass
	<b>f</b> Distance between the floor and the bottom rail of the dropside at its lowest point of the travel shall not be less than 50 mm.	Pass
6.2	<b>Footholds</b> There shall be no structural or components between 150 and 550 mm above the mattress base that could be used as footholds or footholds for climbing	Pass
6.3	<b>Access Fastening Device</b> Any access fastening device shall engage automatically when the dropside is raised and shall consist of : a) two fastening devices separated by a distance of at least 850 mm that have to be operated simultaneously; or b) a system that requires at least two separate but simultaneous actions operating on different principles. c) a system that requires at least two consecutive actions operating on different principles the operation of the second being dependent on the first having been carried out and sustained; or d) Locking mechanisms so constructed that the residual force for operating them is at least 50 N when measured after the test in Appendix E; or	Pass

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [http://www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.